



4 SPEED TRANSMISSION (EX. EQ.)
 P.T.O. OPENING S.A.E. STD. LARGE ON R.H. SIDE.
 GEAR: TRANS. DRIVE 36 T-7P-22 P.A.
 SPEED RATIO 395 R.P.M. TO 1000 R.P.M. ENG.
 ROTATION: OPPOSITE ENGINE.
 ENGINE SPEED GOVERNED AT 3000 R.P.M.

TIRE SIZES	RIM SIZES	A	B	C	D	E	F	G	H	J	K	P
7.00-16 6P S	16 X 5.50	59	61 3/4	27.05						3 1/2	7.60	14.30
7.50-16 6P S	16 X 5.50	59	61 3/4	26.80						3 1/2	8.10	14.70
7.50-16 8P S	16 X 5.50	59	61 3/4	26.77						3 1/2	8.05	14.70
6.00-16 6P D	16 X 4.50	58 1/16			58 3/16	8	27.21	1.61	3	6.65	13.48	83.20
6.50-16 6P D	16 X 4.50	58 1/16			60 3/16	8	26.95	1.10	3	7.05	13.77	83.71
6.00-20 6P D	20 X 5.00	57 1/16			60 3/16	8	27.33	1.86	3	8.90	15.64	82.96

M FRONT SPRINGS

LOAD LBS	RATE LBS PER SPRG	SPRG. NO.
9 1/2	1000	280 1194204
10	1050	467 1194496

L REAR SPRINGS

LOAD LBS	RATE LBS PER SPRG	SPRG. NO.
10 1/16	1950	364 590089
10 1/16	2300	489 1193762
11 3/8	2300	644 590109

BODY BUILDERS LAYOUT
116" W.B.-D-116
126" W.B.-D-126