



FRONT SPRINGS

M	LOAD PER SPRG.	RATE PER INCH	LBS. PER SPRG.	SPRG. N°
12 13/16	2200	579	1261068	
13 9/16	2600	796	1261161	

REAR SPRINGS

L	LOAD PER SPRG.	RATE PER INCH	LBS. PER SPRG.	SPRG. N°
13 9/16	7000	2825	576735	
13 1/16	8500	3420	924313	

TIRE SIZE	RIM SIZE	A	B	C	D	E	F	G	H	P
7.50/20	10P 20X6	70 1/2								
8.25/20	10P 20X6	70 1/2								
8.25/20	12P 20X6	70 1/2								
9.00/20	10P 20X7	68 9/16								
10.00/20	12P 20X7	68 9/16								
10.00/20	12P 20X8	68 1/16								
11.00/20	12P 20X8	68 1/16								
8.25/20	10P 20X6	11	2.07	70 3/8	8.69	25.22	18.07	4	90.30	
8.25/20	12P 20X6	11	2.07	70 3/8	8.69	25.22	18.14	4	90.30	
9.00/20	10P 20X7	13	2.75	70 3/8	9.64	23.56	18.89	4	93.62	
10.00/20	12P 20X7	13	2.38	70 3/8	10.44	23.37	19.68	4 1/2	94.00	
11.00/20	12P 20X8	12.84	1.53	70 3/8	11.09	22.11	21.10	4 1/2	94.52	

NOTE: ABOVE CHART FOR PROD. 21000* G.V.W. JOBS.
FOR EX. EQ. 23000* G.V.W. JOBS ADD 1/2 TO 'D', 'B', 'F', 'B' ADD 1/4 TO 'F'.

BODY BUILDERS LAYOUT
T, TA, V, VA 154", 172", 190" W.B.